



## Anchor, Adapter, SS5/SS150 Twineye

by TTF POWER TECHNOLOGY CO.,LTD

Catalog ID: AA002

Square Shaft & Round Rod Guy Adapter Twineye.

Square Shaft anchors are used in areas where weak soil conditions exist and/or higher holding capacities are required. Extension shafts are added to allow the Lead Section to be installed to the proper depth. The Square Shaft screw anchor system consists of three galvanized components: Lead Section (sold separately), Extension Shaft (sold separately), and the Guy Adapter.

- Guy adapters include a high-strength bolt and nut.
- Forged fittings on both ends of adapters
- Forged integral Pulling Eye speeds up guy installation
- Hot dipped galvanized per ASTM A153

## PRODUCTS DETAILS

### General

Application	Helical Anchoring
Coating	Galvanized, ASTM A-153
Eyenuit Style	Twineye
Strength Note	Ultimate strength ratings apply to properly installed anchors only. Failure to install within 5 ° of alignment with the guy load may significantly lower strength. Note: Pulling Eye Rated: 12,000 lbs. Guy wire should not be attached to pulling eye.
Tensile Strength	70000 lb / 31774.4 kg
Type	Adapters

### Dimensions

Length	18.000 in / 457 mm
Weight	9.565 lb / 4.342 kg

### Logistics

Pallet Quantity	200 EA
Standard Package	5

**For further technical assistance, please contact us**

**TTF POWER TECHNOLOGY CO. , LTD**

Rm. 609-610 Tianjin Technology Financial Building, Tianjin, China, 300384

Phone: +86-22-85233528

Mobile: +86-15510864645

Email: [ttfintlcs@ttfpower.com](mailto:ttfintlcs@ttfpower.com)