



Aluminum Automatic Dead End, #4 - #2 AAC, #4 - #2 AAAC, #4 - #2 ACSR Conductor, Semi-Flex Bail.

by TTF POWER TECHNOLOGY CO.,LTD

Catalog ID: AADE002

Aluminum Automatic Dead End, #4 - #2 AAC, #4 - #2 AAAC, #4 - #2 ACSR Conductor, Diameter range .220 - .250" (5.59 - 8.13 mm), Semi-Flex Bail.

Automatic Dead Ends for ACSR, AAC, and AAAC Conductor galvanized steel stirrup clevis or Z-bail for primary applications and flexible or semi-flex bails for secondary applications

Add "N" for neoprene covered Flex or Semi-flex bail

Add "TA" for pulling eye (clevis bail only)

PRODUCTS DETAILS

General

Bail Option	Semi-Flex Bail
Color Code	Red; Orange
Material	Aluminum
Material - Bail	Stainless Steel
Material - Shell	High Strength Aluminum Alloy
Product Category	Semi-Flex Bail
Type	Automatic

Dimensions

Weight	0.370 lb / 0.168 kg
--------	---------------------

Conductor Related

Conductor Compatibility	ACSR-Swan-4-6/1;ACSR-Sparrow-2-6/1;AAC-Rose-4-7;AAC-Iris-2-7;AAAC 6201 Alloy-Alton-48.69-6/18;AAAC 6201 Alloy-Ames-77.47-6/18
Conductor Diameter - Maximum	0.32
Conductor Diameter - Minimum	0.22
Conductor Diameter Range	0.22 - 0.32

Logistics

Pallet Quantity	4200 EA
-----------------	---------

For further technical assistance, please contact us

TTF POWER TECHNOLOGY CO. , LTD

Rm. 609-610 Tianjin Technology Financial Building, Tianjin, China, 300384

Phone: +86-22-85233528

Mobile: +86-15510864645

Email: ttfintlcs@ttfpower.com