



Anchor, No Wrench, 4in x 54in Tripleye

by TTF POWER TECHNOLOGY CO.,LTD

Catalog ID: ANW001

Chance No-Wrench Screw Anchors may be installed by hand or machine. The eye will also fit into an adapter available from most hole-boringmachine manufacturers so the anchor may be powerinstalled. The entire anchor is hot-dip galvanized for long resistance to rust.

No-Wrench Screw Anchors may be installed by hand or machine.

Hot dipped galvanized per ASTM A153

No-Wrench Screw Anchors can be installed to a greater depth to reach a firmer soil by using an extension rod

PRODUCTS DETAILS

General

Application	Helical Anchoring
Coating	Galvanized, ASTM A-153
Eye Style	Tripleye
Torque Rating	400 ft-lbs
Type	Helical Anchors

Dimensions

Anchor Helix Diameter(s)	4 in / 102 mm
Length	54.000 in / 1372 mm
Rod Diameter	0.750 in / 19 mm
Weight	7.804 lb / 3.542 kg

Logistics

Pallet Quantity	100 EA
Standard Package	1

For further technical assistance, please contact us

TTF POWER TECHNOLOGY CO. , LTD

Rm. 609-610 Tianjin Technology Financial Building, Tianjin, China, 300384

Phone: +86-22-85233528

Mobile: +86-15510864645

Email: ttfintlcs@ttfpower.com