



Auto Splice, Corrosion Resistant, Full Tension for 600 37str, 795 61str AAC, 652.4 740.8AAAC, +556 18/1 - 795 36/1 ACSR

by TTF POWER TECHNOLOGY CO.,LTD

Catalog ID:ASCRFT001

Automatic Splice, Corrosion Resistant, Full Tension, for 600 37str, 795 61 str AAC, 652.4. 740.8 AAAC, +556 18/1 - 795 36/1 ACSR, Dia. Range .879 - 1.041 in

ANSI C119.4

Class A connector

Full tension (95% of conductor rated breaking strength unless noted otherwise)

+ Maximum Design Rating 10,000 lbs (44.5 kN)

Innovative design to help reduce partial tension issues

Indicators deploy upon full conductor insertion

Jaws remain in place until conductor is fully inserted

Simple, smooth installation

PRODUCTS DETAILS

General

Color Code	Natural
Material	Aluminum Alloy
Trade Name	Fargo

Dimensions

Length	27 in / 686 mm
Width	2.3 in / 58 mm

Conductor Related

Conductor Diameter - Maximum	1.041 in / 26 mm
Conductor Diameter - Minimum	0.879 in / 22 mm
Conductor Diameter Range	0.879 - 1.041
Conductor Type	AAC AAAC ACSR

Logistics

Pallet Quantity	224 EA
-----------------	--------

For further technical assistance, please contact us

TTF POWER TECHNOLOGY CO. , LTD

Rm. 609-610 Tianjin Technology Financial Building, Tianjin, China, 300384

Phone: +86-22-85233528

Mobile: +86-15510864645

Email: ttfintlcs@ttfpower.com