



FLAT STEEL CROSSARM BRACE, 34in

SPACING, 32in MOUNTING HOLE SPACING,

1/4in x 1-1/4in MATERIAL SIZE

by TTF POWER TECHNOLOGY CO.,LTD Catalog ID: FSCB014

Flat steel crossarm braces are installed as pairs in a V-type

configuration to the side of crossarm and pole to strengthen the crossarm and provide stability. Order quantity of two for one V-type installation.

- · 7/16" dia. crossarm hole and 9/16" pole hole
- \cdot Rounded brace ends are located 1" from hole centers
- · Material: Galvanized steel per ASTM A-153

PRODUCTS DETAILS

General

| Coating | Galvanized, ASTM A-153 |
|----------|------------------------|
| Material | Steel |

Dimensions

| Distance From Pole | N/A |
|--------------------|--------------------|
| Length | 34.00 in / 864 mm |
| Weight | 2.94 lb / 1.335 kg |

Logistics

Pallet Quantity

750 EA

For further technical assistance, please contact us

TTF POWER TECHNOLOGY CO., LTD

Tianjin Technology And Finance Building

5 N. Meiyuan Road, Huanyuan Industrial Park, Tianjin, China

Phone: +86-22-85233528

Mobile: +86-15510864645

Email: ttfintlcs@ttfpower.com