



Hi*Lite Horizontal Line Post

Insulator

by TTF POWER TECHNOLOGY CO.,LTD

Catalog ID: HLHLPI001

2.5" Line Post, hor. clamp top, Aluminum gain base 12"

CL

Made from tough, durable ESP polymer



PRODUCTS DETAILS

General

Cantilever Bending Strength - Max.	2500 LB / 11348.8 kg
Cantilever Bending Strength - Routine	1250 LB / 567.4 kg
Fitting - Ground End	Al. Gain
Fitting - Live Line End	Clamptop
Material	ESP
Number of Sheds	22
Shed Style	Uniform

Dimensions

Angle	12 °
Diameter - Shed(s)	7.6 IN (193 mm)
Length	14in / 356 mm
Length - Effective	70 in / 178 mm
Rod Diameter	2.5
Thickness - Housing	0.12 in / 3 mm
Width	8.06 in / 205 mm

Electrical Ratings

Arc Distance - Dry	60 IN (1470 mm)
Creep and Leakage Distance	152 IN (3861 mm)
Critical Impulse Flashover (CIFO) - Negative	1035 kV
Critical Impulse Flashover (CIFO) - Positive	930 kV
Flashover Voltage - 60 Hz Dry	600 kV

Flashover Voltage - 60 Hz Wet	520 kV
kV Class	161.00 kV

For further technical assistance, please contact us

TTF POWER TECHNOLOGY CO. , LTD

Rm. 609-610 Tianjin Technology Financial Building, Tianjin, China, 300384

Phone: +86-22-85233528

Mobile: +86-15510864645

Email: ttfintlcs@ttfpower.com