



Hi*Lite Horizontal Line Post

Insulator(A)

by TTF POWER TECHNOLOGY CO.,LTD

Catalog ID: HLHLPI002

3.0" Line Post, 2 hole blade, Aluminum gain base 14" CL

1" bolts

Made from tough, durable ESP polymer



PRODUCTS DETAILS

General

Cantilever Bending Strength - Max.	2600 LB / 1180.192 kg
Cantilever Bending Strength - Routine	1300 LB / 590.096 kg
Fitting - Ground End	Al. Gain
Fitting - Live Line End	Two Hole Blade
Material	ESP
Number of Sheds	38
Shed Style	Uniform

Dimensions

Angle	14 °
Diameter - Shed(s)	9.3 IN (228.8 mm)
Length	17 in / 432 mm
Length - Effective	111 in / 2819 mm
Rod Diameter	3
Thickness - Housing	> 3MM
Width	8.07 in / 205 mm

Electrical Ratings

Arc Distance - Dry	103 IN (2,616 mm)
Creep and Leakage Distance	297 IN (7,544 mm)
Critical Impulse Flashover (CIFO) - Negative	1695 kV
Critical Impulse Flashover (CIFO) - Positive	1625 kV
Flashover Voltage - 60 Hz Dry	960 kV

Flashover Voltage - 60 Hz Wet	835 kV
kV Class	345.00 kV

For further technical assistance, please contact us

TTF POWER TECHNOLOGY CO. , LTD

Rm. 609-610 Tianjin Technology Financial Building, Tianjin, China, 300384

Phone: +86-22-85233528

Mobile: +86-15510864645

Email: ttfintlcs@ttfpower.com