



Hot Line Tap Clamp, Aluminum



by TTF POWER TECHNOLOGY CO.,LTD

Catalog ID: HLTC001

Overhead Primary Tap, Hot Line Tap Clamp, Aluminum, AAC|AAAC|ACSR, Range 0.157 - 0.905 in

High pressure developed by eyestem, lock washer assures permanent connection.

PRODUCTS DETAILS

General

Inhibitor Loaded	No
Material	Aluminum Alloy
Material - Body	Aluminum Alloy
Material - Eyebolt	Tin Plated Bronze
Material - Eyestem	Stainless Steel
Material - Hex Nut	Stainless Steel
Material - Keeper	Aluminum Alloy
Material - Spring (on Eyestem)	Stainless Steel
Material - Washer	Stainless Steel
Plating	No

Dimensions

Height	7.88 in / 200 mm
Weight	0.706 lb / 0.320 kg
Width	1.75 in / 44 mm

Conductor Related

Conductor Diameter (Main) - Maximum	0.905 in / 230 mm
Conductor Diameter (Main) - Minimum	0.157 in / 4 mm
Conductor Diameter (Main) Range	0.157 - 0.905
Conductor Diameter (Tap) - Maximum	0.593 in / 15 mm
Conductor Diameter (Tap) - Minimum	0.157 in / 4 mm
Conductor Type	Aluminum

Logistics

Packaging Type	Box
Pallet Quantity	2400

For further technical assistance, please contact us

TTF POWER TECHNOLOGY CO. , LTD

Rm. 609-610 Tianjin Technology Financial Building, Tianjin, China, 300384

Phone: +86-22-85233528

Mobile: +86-15510864645

Email: ttfintlcs@ttfpower.com