



Hot Line Tap Clamp, Aluminum(A)



by TTF POWER TECHNOLOGY CO.,LTD

Catalog ID: HLTC002

Overhead Primary Tap, Hot Line Tap Clamp, Aluminum, AAC|AAAC|ACSR, Range 0.502 - 1.031 in

High pressure developed by eyestem, lock washer assures permanent connection.

PRODUCTS DETAILS

General

Bolt Installation Torque (Recommended)	0 ft-lbs
Material	Aluminum Alloy
Material - Body	Aluminum Alloy
Material - Eyebolt	Tin Plated Bronze
Material - Eyestem	Forged Silicon Bronze
Material - Hex Nut	Stainless Steel
Material - Spring (on Eyestem)	Stainless Steel
Material - Washer	Stainless Steel
Plating	No

Dimensions

Weight	0.850 lb / 0.386 kg
--------	---------------------

Conductor Related

Conductor Diameter (Tap) - Maximum	0.703 in / 18 mm
Conductor Diameter (Tap) - Minimum	0.198 in / 5 mm
Conductor Diameter - Maximum	1.031
Conductor Diameter - Minimum	0.502
Conductor Diameter Range	0.502 - 1.031

Logistics

Packaging Type	Box
Pallet Quantity	1800

For further technical assistance, please contact us

TTF POWER TECHNOLOGY CO. , LTD

Rm. 609-610 Tianjin Technology Financial Building, Tianjin, China, 300384

Phone: +86-22-85233528

Mobile: +86-15510864645

Email: ttfintlcs@ttfpower.com