



Optima Arrester (10.2 kV MCOV, 7214 Hardware)

by TTF POWER TECHNOLOGY CO.,LTD

Catalog ID: OA002

IEEE Heavy Duty / IEC Distribution High Polymer Housed Surge Arrester

- Reliable capacitive disconnecter operates at fault currents as low as 1 Amp
- Dynamic triple sealing system protects internal components from moisture ingress to extend service lifetime
- High quality MOV discs made in Wadsworth, Ohio since 1978
- Arresters assembled in Aiken, South Carolina
- 100% routine tested

PRODUCTS DETAILS

General

Application	Distribution
Bracket Type	None
Cantilever Bending Strength - Max.	80 Nm
Color	Gray Housing
Mounting Position	Upright
Type	Distribution

Dimensions

Height	5.5 in / 140 mm
Stud Type	3/8-16

Electrical Ratings

Creep and Leakage Distance	17 in (431 mm)
Current - Low Current Long Duration (LCLD) Test	250 A
Duty Cycle	12 kV
Frequency Rating	48-62 Hz
MCOV	10.2 kV
Maximum .5 Microsecond Discharge Volts @ Classifying Current	42.1 kV
Maximum Discharge Voltage	<ul style="list-style-type: none"> · 30.4 kV @ 1.5 kA · 32.6 kV @ 3 kA · 34.5 kV @ 5 kA · 37.6 kV @ 10 kA · 42.7 kV @ 20 kA

	· 50.3 kV @ 40 kA
Maximum Switching Surge Protective Level @ 500A	27.8 kV
Minimum Strike	6.6 in / 168 mm
Pressure Relief Capability-Symmetrical rms (kA)	20
Time - Low Current Long Duration (LCLD) Test	2000 μ s

Certifications and Compliance

Industry Standard(s)	IEEE/IEC
----------------------	----------

Logistics

Pallet Quantity	192 EA
-----------------	--------

For further technical assistance, please contact us

TTF POWER TECHNOLOGY CO. , LTD

Rm. 609-610 Tianjin Technology Financial Building, Tianjin, China, 300384

Phone: +86-22-85233528

Mobile: +86-15510864645

Email: ttfintlcs@ttfpower.com