



## Rod, Expanding/Cross-Plate Anchor, 1/2in X 6ft Thimbleye

by TTF POWER TECHNOLOGY CO.,LTD

Catalog ID: RECA002

Expanding/Cross-Plate Anchor Rod 0.5" (12.7 mm) Diameter Rod, 6' (1829 mm) long with Thimbleye.

Anchor rod used with Expanding and Cross-plate anchors are available for one, two, or three guys. Thimbleye, Twineye and Tripleye eye design distribute pulling stresses uniformly over individual strands of guy wire and keep the guy wire from spreading, kinking, or bending. The drop-forged eye of each anchor rod is stronger than the rod itself. Rod length and diameter are stamped below each rod eye. Each rod is threaded 3-1/2" minimum length. Heavy square nut included.

- Hot dipped galvanized per ASTM A153
- Square nut assembled to rod
- Rods used with Cross-plate and Expanding anchors

## PRODUCTS DETAILS

### General

Application	Earth Tension Anchoring
Coating	Galvanized, ASTM A-153
Eyenuit Style	Thimbleye
Strength Note	Ultimate strength ratings apply to properly installed anchors only. Failure to install within 5 ° of alignment with the guy load may significantly lower strength.
Tensile Strength	10000 lb / 45392 kg
Type	Anchor Rod

### Dimensions

Length	72.000 in / 1829 mm
Rod Diameter	0.500 in / 13 mm
Weight	4.410 lb / 2.002 kg

### Logistics

Pallet Quantity	150 EA
Standard Package	10

**For further technical assistance, please contact us**

**TTF POWER TECHNOLOGY CO. , LTD**

Rm. 609-610 Tianjin Technology Financial Building, Tianjin, China, 300384

Phone: +86-22-85233528

Mobile: +86-15510864645

Email: [ttfintlcs@ttfpower.com](mailto:ttfintlcs@ttfpower.com)