



## SPOOL INSULATOR DEADEND CLEVIS, SWINGING STYLE



by TTF POWER TECHNOLOGY CO.,LTD

Catalog ID: SIDC001

Clevis bracket for spool insulators used in secondary deadend applications. Minimum ultimate deadend strength is 2,000 lbs. Used with ANSI Class 53-1 spool insulators. Replacement components: clevis pin - P2070061; cotter pin - 056746P.

23/64" dia. clevis pin with self-locking cotter pin

Hot dip galvanized per ASTM A-153

Manufactured in compliance with ANSI/IEEE C135.20

## PRODUCTS DETAILS

### General

Coating	Galvanized, ASTM A-153
Material	Steel
Style	Clevis Only (less mounting bracket)
Type	Insulated Secondary Clevis

### Dimensions

Distance From Pole	N/A
Height	2.25 in / 57 mm
Length	2.50 in / 64 mm
Weight	0.4 lb / 0.182 kg

### Certifications and Compliance

RUS Listed Reference	as - Clevis, service swinging
----------------------	-------------------------------

### Logistics

Pallet Quantity	4000 EA
-----------------	---------

For further technical assistance, please contact us

**TTF POWER TECHNOLOGY CO. , LTD**

Rm. 609-610 Tianjin Technology Financial Building, Tianjin, China, 300384

Phone: +86-22-85233528

Mobile: +86-15510864645

Email: [ttfintlcs@ttfpower.com](mailto:ttfintlcs@ttfpower.com)