13.2 KV(Line Voltage) Line Surge Arrester

Catalog ID: 08B2D0F

Line Surge Arrester
Custom designs available up to 765 kV

PRODUCT DETAILS

General

Application	35 kV and Below
Type	Line Arresters

Electrical Ratings

Creep and Leakage Distance	17.0 in (431.8 mm)
Duty Cycle	12 kV
Frequency Rating	48-62 Hz
MCOV	10.2 kV
Maximum .5 Microsecond Discharge Volts @ Classifying Current	40.4 kV
Maximum Discharge Voltage	30.3 kV @ 1.5 kA 32.3 kV @ 3 kA 34.2 kV @ 5 kA 37.6 kV @ 10 kA 42.3 kV @ 20 kA 50.3 kV @ 40 kA
Maximum Switching Surge Protective Level @ 500A	29.0 kV
Pressure Relief Capability-Symmetrical rms (kA)	20
Voltage – Line	13.2 kV

Certifications and Compliance

Industry Standard(s)	IEEE/IEC

RESOURCES AND DOWNLOADS

Specifications	Download PDF
Technical Drawings	Download PDF

For further technical assistance, please contact us

TTF Power Technology Co., Ltd.

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384
Landline: (+86) 22-8523-3528
Cell / WhatsApp: (+86) 155-1086-4645
Email: sales@ttfpower.com
Website: https://ttfpower.com