



## 15 kV, 110 kV BIL, D-shape Linkbreak Type C Polymer Cutout with a 100A, 10kAIC Fuseholder

Catalog ID: 02B0Q8F

D-shape Fuse Holder for pole mounting  
 BIL: 15 kV, 110 kV  
 Type: Cutout



### PRODUCT DETAILS

#### General

<b>Bracket Type</b>	<b>NEMA “B” Heavy Duty for crossarm</b>
Description – Replacement Fuse Holder	T720-112T
Type	Cutout

#### Electrical Ratings

<b>BIL</b>	<b>110 kV</b>
Creep and Leakage Distance	12.6” (319mm)
Current Rating	100 A
Fuselink Current Range	1A to 100A
Reference Voltage Limit – Minimum	Thru 14.4kV
Temperature Rise – Max. at 300A	38° C
Voltage – Maximum	15 kV
Voltage – Radio Interference	Ambient @ 9.41kV
Voltage Rating	15 kV

#### Logistics

Standard Package	1
------------------	---

### RESOURCES AND DOWNLOADS

Specifications	<a href="#">Download PDF</a>
Technical Drawings	<a href="#">Download PDF</a>

*For further technical assistance, please contact us*

**TTF Power Technology Co., Ltd.**

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384

Landline: (+86) 22-8523-3528

Cell / WhatsApp: (+86) 155-1086-4645

Email: [sales@ttfpower.com](mailto:sales@ttfpower.com)

Website: <https://ttfpower.com>