



Aluminum Alloy Hot Line Tap Clamp

Catalog ID: 05D6G2N

A hotline tap clamp is a gadget used to fix between a Hot Line and Transformer. It has high corrosion resistance and high mechanical strength.

Material: Aluminum Alloy



PRODUCT DETAILS

General

Material	Aluminum Alloy
Material – Body	Aluminum Alloy
Material – Eyebolt	Tin Plated Bronze
Material – Eystem	Forged Silicon Bronze
Material – Hex Nut	Stainless Steel
Material – Spring (on Eystem)	Stainless Steel
Material – Washer	Stainless Steel
Weight	0.392 lb (0.18 kg)

Electrical Ratings

Maximum Current Rating Amps Continuous	Rated for maximum rating of largest tap conductor in range
--	--

Conductor Related

Conductor Compatibility	ACSR-Turkey-6-6/1;ACSR-Swan-4-6/1;ACSR-Swanate-4-7/1;ACSR-Sparrow-2-6/1;ACSR-Sparate-2-7/1;ACSR-Robin-1-6/1;ACSR-Raven-1/0-6/1;AAC-Peachbell-6-7;AAC-Rose-4-7;AAC-Iris-2-7;AAC-Pansy-1-7;AAC-Poppy-1/0-7;AAC-Aster-2/0-7;AAAC 6201 Alloy-Akron-30.58-6/18;AAAC 6201 Alloy-Alton-48.69-6/18;AAAC 6201 Alloy-Ames-77.47-6/18;AAAC 6201 Alloy-Azusa-123.3-6/18
Conductor Diameter (Tap) – Maximum	0.438 in (11.13 mm)
Conductor Diameter (Tap) – Minimum	0.128 in (3.25 mm)
Conductor Diameter – Maximum	0.414
Conductor Diameter – Minimum	0.128
Conductor Diameter Range	0.128 – 0.414

Logistics

Packaging Type	Box
----------------	-----

RESOURCES AND DOWNLOADS

Specifications

[Download PDF](#)

Technical Drawings

[Download PDF](#)

For further technical assistance, please contact us

TTF Power Technology Co., Ltd.

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384

Landline: (+86) 22-8523-3528

Cell / WhatsApp: (+86) 155-1086-4645

Email: sales@ttfpower.com

Website: <https://ttfpower.com>