



Cable Spacer, Range 1.289 in – 1.459 in

Catalog ID: 05F5U4H

Cable Spacer
keep the spacing between the bundle conductors
For limited current use like lightning arrester tap



PRODUCT DETAILS

General

Material	Aluminum
Material – Clamping Hardware	Aluminum Alloy
Type	Cable Spacer

Dimensions

Angle – Pad	180 °
Base Hole Spacing	0 in
Length Before Compression	0 in
Weight	3.136 lb (1.42 kg)
Width – Pad	4 in (101.6 mm)

Conductor Related

Conductor Compatibility	ACSR-Finch-1113-54/19;ACSR-Bunting-1192.5-45/7;ACSR-Grackle-1192.5-54/19;ACSR-Bittern-1272-45/7;ACSR-Pheasant-1272-54/19;ACSR-Dipper-1351.5-45/7;ACSR-Martin-1351.5-54/19;ACSR-Bobolink-1431-45/7;AAC-Narcissus-1272-61;AAC-Columbine-1351.5-61;AAC-Carnation-1431-61;AAC-Gladiolus-1510.5-61;AAC-Coreopsis-1590-61
Conductor Diameter – Maximum	1.459 in (37.06 mm)
Conductor Diameter – Minimum	1.289 in (32.74 mm)
Conductor Diameter Range	1.289 – 1.459
Conductor Spacing	8 in (203.2 mm)
Conductor Type	AAC ACSR

RESOURCES AND DOWNLOADS

Specifications	Download PDF
Technical Drawings	Download PDF

For further technical assistance, please contact us

TTF Power Technology Co., Ltd.

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384

Landline: (+86) 22-8523-3528

Cell / WhatsApp: (+86) 155-1086-4645

Email: sales@ttfpower.com

Website: <https://ttfpower.com>