



Cast Epoxy Station Post, 200KV BIL

Catalog ID: 07F5A2M

Station Post
Can be mounted upright or underhung



PRODUCT DETAILS

General

Application	Station Post
Bottom Terminal Type	Threaded Inserts
Cantilever Bending Strength – Max.	2000
Color	Gray
Compressive Strength	15000 lb
Material – Insulation	APG-02 – Cycloaliphatic Epoxy
Mounting Position	Vertical to Horizontal
Number of Bolt Holes – Bottom Terminal	4
Number of Bolt Holes – Top Terminal	4
Plating – Bottom Terminal	Zinc Plated
Tensile Strength	7,000 lb
Top Terminal Plating	Zinc Plated
Top Terminal Type	Threaded Inserts
Torsional Strength	10,000 lb
Type	Cast Epoxy

Dimensions

Bottom Terminal Diameter	4.72 in
Diameter – Bottom Terminal Bolt Circle	3.00 in
Diameter – Bottom Terminal Bolt Holes	1/2-13
Diameter – Large Shed	6.93 in
Diameter – Top Terminal Bolt Circle	3.00 in
Diameter – Top Terminal Bolt Holes	1/2-13
Diameter – Top Terminal Outside	4.72 in
Length	15 in
Weight	17.4 lb

Electrical Ratings

BIL	200 kV
Minimum Creepage	38 in
Minimum Strike	15.0 in
kV Class	34.5 kV

Certifications and Compliance

Industry Standard(s)	ANSI C29.8
----------------------	------------

RESOURCES AND DOWNLOADS

Specifications	Download PDF
Technical Drawings	Download PDF

For further technical assistance, please contact us

TTF Power Technology Co., Ltd.

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384

Landline: (+86) 22-8523-3528

Cell / WhatsApp: (+86) 155-1086-4645

Email: sales@ttfpower.com

Website: <https://ttfpower.com>