



Expanding Rock Anchor, 0.75 in Dia Rod, 15 in Length with Triple Eye

Catalog ID: 03G8P4V

Expanding Rock Anchor stabilize and steady the power pole.

Application: Earth Tension Anchoring Coating: Galvanized, ASTM A-153

Eyenut Style: Tripleye



PRODUCT DETAILS

General

Application	Earth Tension Anchoring
Coating	Galvanized, ASTM A-153
Eyenut Style	Tripleye
Strength Note	Ultimate strength ratings apply to properly installed anchors only. Failure to install within 5° of alignment with the guy load may significantly lower strength. Recommended minimum installation depth is 12" in solid rock.
Tensile Strength	23000 lb
Туре	Rock Anchors
Dimensions	
Anchor Hole Size	2 in (50.8 mm)
Diameter	1.75 in (44.450 mm)
Length	15.000 in (381.000 mm)
Rod Diameter	0.750 in (19.050 mm)
Weight	4.900 lb (2.223 kg)
Certifications and Compliance	
RUS Listed Reference	z – Anchors, Rock
Logistics	
Pallet Quantity	500
Standard Package	5

RESOURCES AND DOWNLOADS

Specifications	Download PDF
Technical Drawings	Download PDF

For further technical assistance, please contact us

TTF Power Technology Co., Ltd.

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384

Landline: (+86) 22-8523-3528

Cell / WhatsApp: (+86) 155-1086-4645

Email: sales@ttfpower.com Website: https://ttfpower.com