



Fiberglass Secondary Connector or Sectionalizer, Length 18.8 in

Catalog ID: 05C706V



Secondary Connector is used for sectionalizing a secondary conductor.

Description – End Fitting: HDG Ductile Iron

Strength Rating – Minimum Ultimate, Longitudinal (L): 6000 lb

PRODUCT DETAILS

General

| | |
|--|------------------|
| Description – End Fitting | HDG Ductile Iron |
| EU RoHS Indicator | No |
| Strength Rating – Minimum Ultimate, Longitudinal (L) | 6000 lb |

Dimensions

| | |
|---------------------------|---------------------|
| Diameter – Rod / Tube | 0.625 in (15.88 mm) |
| Distance From Pole | 18.8 in (477.52 mm) |
| Length | 18.8 in (477.52 mm) |
| Radius – FWDE Wrap-Around | 0.625 |
| Weight | 4.0 lb (1.81 kg) |

Logistics

| | |
|------------------|-----|
| Pallet Quantity | 360 |
| Standard Package | 1 |

RESOURCES AND DOWNLOADS

| | |
|--------------------|------------------------------|
| Specifications | Download PDF |
| Technical Drawings | Download PDF |

For further technical assistance, please contact us

TTF Power Technology Co., Ltd.

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384

Landline: (+86) 22-8523-3528

Cell / WhatsApp: (+86) 155-1086-4645

Email: sales@ttfpower.com
Website: <https://ttfpower.com>