



Helical Anchoring with Double Eyes

Catalog ID: 03C9U7M

Helical Anchoring
 Guy adapters include a high-strength bolt and nut.
 Forged fittings on both ends of adapters
 Forged integral Pulling Eye speeds up guy installation



PRODUCT DETAILS

General

Application	Helical Anchoring
Coating	Galvanized, ASTM A-153
Eyenuit Style	Double eye
Strength Note	Ultimate strength ratings apply to properly installed anchors only. Failure to install within 5 ° of alignment with the guy load may significantly lower strength. Note: Pulling Eye Rated: 12,000 lbs. Guy wire should not be attached to pulling eye.
Tensile Strength	70000 lb (31751.47 kg)
Type	Adapters

Dimensions

Length	18.000 in (457.2 mm)
Weight	9.565 lb (4.34 kg)

Certifications and Compliance

RUS Listed Referencez – Anchors	Power-installed screw
---------------------------------	-----------------------

Logistics

Pallet Quantity	200
Standard Package	5

RESOURCES AND DOWNLOADS

Specifications	Download PDF
Technical Drawings	Download PDF

For further technical assistance, please contact us

TTF Power Technology Co., Ltd.

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384

Landline: (+86) 22-8523-3528

Cell / WhatsApp: (+86) 155-1086-4645

Email: sales@ttfpower.com

Website: <https://ttfpower.com>