



Silicone Polymer Deadend, 15,000 lb

Catalog ID: 07B2H2S

Silicone Polymer Deadend
Detailed specifications are in the PDF below



PRODUCT DETAILS

General

Application	Deadend
Cantilever Bending Strength – Routine	7500
Fitting – Ground/Base	Clevis
Fitting – Live Line End	Tongue
Insulator Type	N/A
Material	Silicone Polymer
Material – End Fitting	Steel
Material – Pin (Cotter)	Stainless Steel
Number of Sheds	8
Shed Style	Uniform
Strength Rating – Ultimate	15000 lb
Tensile Strength	15 K
Tensile Strength – Routine	7500

Dimensions

Diameter – Shed(s)	3
Length – Effective	25.0 in
Rod Diameter	0.625
Thickness – Housing	0.148
Weight	2.94 lb

Electric Ratings

Arc Distance – Dry	20
Creep and Leakage Distance	33 IN (838 mm)
Critical Impulse Flashover (CIFO) – Negative	360
Critical Impulse Flashover (CIFO) – Positive	325
Flashover Voltage – 60 Hz Dry	200

Flashover Voltage – 60 Hz Wet	160
Voltage – Line	35000 V
Withstand Voltage – 60 Hz Dry	170
Withstand Voltage – 60 Hz Wet	130

Logistics

Pallet Quantity	300
Standard Package	15

RESOURCES AND DOWNLOADS

Specifications	Download PDF
Technical Drawings	Download PDF

For further technical assistance, please contact us

TTF Power Technology Co., Ltd.

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384

Landline: (+86) 22-8523-3528

Cell / WhatsApp: (+86) 155-1086-4645

Email: sales@ttfpower.com

Website: <https://ttfpower.com>