



Silicone Polymer Line Post Insulator, 600-700 KV

Catalog ID: 07H7C2M

Line Post Insulator
made by durable, high quality silicone polymer



PRODUCT DETAILS

General

Cantilever Bending Strength – Max.	2140 LB
Cantilever Bending Strength – Routine	1070 LB
Fitting – Ground End	Al. Gain
Fitting – Live Line End	Clamptop
Number of Sheds	26
Shed Style	Uniform

Dimensions

Angle	12 °
Diameter – Shed(s)	7.6 IN (193 mm)
Length	14 in
Length – Effective	81 in
Rod Diameter	2.5
Thickness – Housing	0.12 in
Width	8.06 in

Electrical Ratings

Arc Distance – Dry	71 IN (1739.5 mm)
Creep and Leakage Distance	180 IN (4572 mm)
Critical Impulse Flashover (CIFO) – Negative	1195 kV
Critical Impulse Flashover (CIFO) – Positive	1095 kV
Flashover Voltage – 60 Hz Dry	700 kV
Flashover Voltage – 60 Hz Wet	600 kV
kV Class	230.00 kV

RESOURCES AND DOWNLOADS

Specifications	Download PDF
----------------	------------------------------

For further technical assistance, please contact us

TTF Power Technology Co., Ltd.

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384

Landline: (+86) 22-8523-3528

Cell / WhatsApp: (+86) 155-1086-4645

Email: sales@ttfpower.com

Website: <https://ttfpower.com>