


CATALOG NUMBER : 03G9N1T

NOTES:

- 1.MATERIAL: STEEL ANCHOR ROD AND HARDWARE. DUCTILE IRON CASTINGS PER ASTM A536.
- 2.FINISH: HOT DIP GALVANIZE PER ASTM A123/A153(LATEST REV.)SLIP WASHERS ARE ZINC PLATED FOR EASE OF INSTALLATION.
- 3.ROCK HOLE: PRECISELY DRILLED ROCK HOLES +/-1/16" PER THE INCLUDED TABLE ARE ESSENTIAL FOR PROPER FUNCTION.RECOMMENDED MINIMUM INSTALLATION DEPTH IS 12".
- 4.ROCK TYPE: HEAVY ROCK ANCHORS ARE DESIGNED FOR USE WITH VARY HARD ROCK TYPES WHERE OTHER ROCK ANCHORS CAN'T REACH THE MAXIMUM RATING.
- 5.PRELOAD: WEDGE-STYLE ANCHORS WILL TIGHTEN BY SLIDING AS LOAD IS INCREASED. FOR APPLICATIONS WHERE NO MOVEMENT IS ALLOWABLE, PRODUCT MUST BE PRELOADED TO DESIGN LOAD.
- 6.GROUT: GROUT BACKFILL IS ALWAYS RECOMMENDED WHEN POSSIBLE FOR ROCK ANCHOR INSTALLATIONS.



LENGTH"L"	ROD DIAMETER"D"	RATING	DRILLED ROCK HOLE SIZE
15	.75	23000LB	2.00

DRN BY:	DATA
Ella	07/09/16
<small>CONFIDENTIAL THIS DRAWING AND ITS CONTENTS PROPERTY OF TIANJIN TUOFA ELECTRIC POWER TECHNOLOGY CO.,LTD. NO PUBLICATION, DISTRIBUTION OR COPIES MAY BE MADE WITHOUT THE WRITTEN CONSENT OF TIANJIN TUOFA ELECTRIC POWER TECHNOLOGY CO.,LTD. TIANJIN TUOFA ELECTRIC POWER TECHNOLOGY CO.,LTD UNPUBLISHED ALL RIGHTS RESERVED UNDER THE COPYRIGHT LAWS.</small>	

GALVANIZED ROCK ANCHORS WITH TRIPLE EYE



TTF POWER TECHNOLOGY CO.