6" TO 14" **BOLT CIRCLE** 3 (330.2mm) SQUARE 3.6" DIA. CENTER HOLE **SLOT FOR** .75" BOLT TAP .5-13UNC (1219.2mm)75 (19.1mm) 4" DIA. O. D. .226" WALL THICKNESS 48 1.5 (38.1mm) NOTE-4 84 (2133.6mm) 10" DIA (76.2 mm)**HELIX** (152.4mm

CATALOG NUMBER: 03D5X4G

NOTES:

- 1.FINISH: HOT DIP GALVANIZE PER ASTM A153(LATEST REVISION).
- 2.BASEPLATE TO BE PERPENDICULAR TO SHAFT AXIS(±1°) AND HOLE CENTERLINE CONCENTRIC (±.188) TO SHAFT AXIS.
- 3.STENCIL MIN. 1/2 IN. LETTERS MANUFACTURER'S NUMBER AFTER GALVANIZING.
- 4.FLAME CUT TWO SLOTS IN SHAFT PERPENDICULAR THE BASEPLATE, HELIX, AND PILOT POINT ON ALL WELDED AREAS.
- 5.PREHEAT, TUMBLEBLAST, HANDGRIND, AND CLEAN BASEPLATE, HELIX, AND PILOT POINT ON ALL WELDED AREAS.
- 6.FLAMECUT IRREGULARITIES NOT TO EXCEED 1/32 IN. ABOVE NOMINAL SURFACE LEVEL OR INTERSECTIONS OF NOMINAL SURFACES.
- 7.MANUFACTURER TO HAVE IN EFFECT INDUSTRY RECOGNIZED WRITTEN QUALITY CONTROL FOR ALL MATERIALS AND MANUFACTURING PROCESSES.
- 8.ALL MATERIAL IS TO BE NEW, UNUSED AND MILL TRACEABLE METING THE FOLLOWING SPECIFICATIONS:

BASEPLATE: ASTM A36-(LATEST REVISION) HOT ROLLED STEEL PLATE

SHAFT: STEEL TUBING PER ASTM 500 GRADE B.

HELIX: ASTM A635(LATEST REVISION) HOT ROLLED STEEL.

| DRN BY: | DATA |
|---------|----------|
| Ella | 10/08/16 |

CONFIDENTIAL-THIS DRAWING AND IN CONTENTS POPERTY OF TANNIN TUOFA ELECTRIC POWER TECHNOLOGY CO.LTD. NO PUBLICATION, DISTRIBUTION OR COPES MAY BE MADE WITHOUT THE WRITTEN CONSENT OF THANIN TUOFA ELECTRIC POWER TECHNOLOGY CO.LTD. THANIN TUOFA ELECTRIC POWER TECHNOLOGY CO.LTD. UNEVELSHED ALL RIGHTS RESERVED UNDER THE COPYRIGHT LAWS.

LIGHTING FOUNDATION ANCHORS WITH 4 BOLT SLOTS



TTF POWER TECHNOLOGY CO.