CATALOG NUMBER: 03E5T2L .44 (36.6mm) .62 (41.1mm) 3.27 (83.1mm) **SECTION A-A SECTION B-B** 1.69 (42.9mm) STAMPED IN THIS В APPROXIMATE LOCATION 2.85 (72.4mm) 2.17 (55.1mm) 82 (46.2mm) 61 (40.9mm - R .28 (R 7.1mm) 1.25 (31.8mm) - R .25 (R 6.4mm) (OUTER THIMBLES) 69 (1752.6mm) ∠ 1" HEX BOLT AND JAM NUT

NOTES:

- 1.ULTIMATE TENSION CAPACITY RATING: 58,000 LB. FAILURE TO ALIGN ROD WITHIN 5 DEGREES OF LOAD MAY SIGNIFICANTLY REDUCE CAPACITY.
- 2.ROD MATERIAL:LOW CARBON STEEL.
- 3.FINISH: HOT-DIP GALVANIZED PER ASTM A153(LAST RECISION).

DRN BY:	DATA
Ella	07/09/16

CONFIDENTIAL THIS DRAWING AND ITS CONTENTS PROPERTY OF THANIN TUGFA ELECTRIC POWER TECHNOLOGY CO...TD. NO PUBLICATION.

OLITION OF PUBLICATION.

ANDE WITHOUT THE WRITTEN CONSENT OF THANIN TUGFA ELECTRIC POWER TECHNOLOGY CO...LTD. THANIN TUGFA ELECTRIC POWER TECHNOLOGY CO...LTD. UNFURLISHED ALL RIGHTS RESERVED UNDER THE CONTENT OF THE

NO WRENCH HELICAL ANCHORS TRIPLE EYES



TTF POWER TECHNOLOGY CO.