



15 kV, 110 kV BIL, D-shape Linkbreak Type C Porcelain Cutout with a 100A, 10kAIC Fuseholder

Catalog ID: 02B7D2U

Link Break Cutout Fuse
 Stops the progression of energy
 Safeguard circulation transformers from current floods and over-burdens
 Used on overhead transmission lines
 A type of power line hardware



PRODUCT DETAILS

General

Bracket Type	NEMA “B” Heavy Duty for crossarm
EU RoHS Indicator	No
Type	Cutout

Dimensions

Weight	18.542 lb (8.41 kg)
--------	---------------------

Electric Ratings

BIL	110 kV
Creep and Leakage Distance	8.7 in (220mm)
Current Rating	100 A
Fuselink Current Range	1A to 100A
Reference Voltage Limit – Minimum	Thru 14.4kV
Temperature Rise – Max. at 300A	38° C
Voltage – Maximum	15 kV
Voltage – Radio Interference	Ambient @ 9.41kV
Voltage Rating	15 kV

Logistics

Pallet Quantity	72
Standard Package	1

RESOURCES AND DOWNLOADS

Specifications	Download PDF
----------------	--------------

For further technical assistance, please contact us

TTF Power Technology Co., Ltd.

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384

Landline: (+86) 22-8523-3528

Cell / WhatsApp: (+86) 155-1086-4645

Email: sales@ttfpower.com

Website: <https://ttfpower.com>