



## Aluminum Alloy Splice, Diameter Range: 0.659 in – 0.724 in

Catalog ID: 01C0Q2N

Splice

Industrial standard ANSI C119.4

A super durable or impermanent association on AAC, ACSR or AAAC conductor

Conductor type 397.5, 336.4 AAC, 394.5 AAAC, 336.4(18/1) ACSR

Applications on full or partial tension

Against corrosion



### PRODUCT DETAILS

#### General

Color Code	Green
Material	Aluminum Alloy

#### Conductor Related

Conductor Diameter – Maximum	0.724 in (18.39 mm)
Conductor Diameter – Minimum	0.659 in (16.74 mm)
Conductor Diameter Range	0.659 in – 0.724 in
Conductor Type	AAC, AAAC, ACSR

### RESOURCES AND DOWNLOADS

Specifications	<a href="#">Download PDF</a>
Technical Drawings	<a href="#">Download PDF</a>

*For further technical assistance, please contact us*

#### TTF Power Technology Co., Ltd.

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384

Landline: (+86) 22-8523-3528

Cell / WhatsApp: (+86) 155-1086-4645

Email: [sales@ttfpower.com](mailto:sales@ttfpower.com)

Website: <https://ttfpower.com>