



Aluminum Cable Spacer

Catalog ID: 05F7U4A

Aluminum Cable Spacer is an electrical distribution system designed for high reliability, low operating costs, and improved right-of-way flexibility. It is designed for take control of the flow of electrical current in power system. Made of Aluminum Alloy for making a protective layer of oxide on the surface of air exposure



PRODUCT DETAILS

General

Material	Aluminum
Material – Clamping Hardware	Aluminum Alloy
Type	Cable Spacer

Dimensions

Angle – Pad	180 °
Weight	3.920 lb (1.78 kg)
Width – Pad	4 in (101.6 mm)

Conductor Related

Conductor Compatibility	ACSR-Finch-1113-54/19;ACSR-Bunting-1192.5-45/7;ACSR-Grackle-1192.5-54/19;ACSR-Bittern-1272-45/7;ACSR-Pheasant-1272-54/19;ACSR-Dipper-1351.5-45/7;ACSR-Martin-1351.5-54/19;ACSR-Bobolink-1431-45/7;AAC-Narcissus-1272-61;AAC-Columbine-1351.5-61;AAC-Carnation-1431-61;AAC-Gladiolus-1510.5-61;AAC-Coreopsis-1590-61
Conductor Diameter – Maximum	1.459 in (37.06 mm)
Conductor Diameter – Minimum	1.289 in (32.74 mm)
Conductor Diameter Range	1.289 – 1.459
Conductor Spacing	12 in (304.8 mm)
Conductor Type	AAC ACSR

RESOURCES AND DOWNLOADS

Specifications	Download PDF
Technical Drawings	Download PDF

For further technical assistance, please contact us

TTF Power Technology Co., Ltd.

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384

Landline: (+86) 22-8523-3528

Cell / WhatsApp: (+86) 155-1086-4645

Email: sales@ttfpower.com

Website: <https://ttfpower.com>