



Aluminum Cable Spacer, 3.92 lb

Catalog ID: 05F4I2U

Cable Spacer

a pre-designed electrical dispersion framework intended for high dependability

low working expenses

worked on option to proceed adaptability

Spacing 12 in

range 1.632 in – 1.824 in



PRODUCT DETAILS

General

EU RoHS Indicator	No
Material	Aluminum
Material – Clamping Hardware	Aluminum Alloy
Number of Ground Braid Lug Holes	0
Type	Cable Spacer

Dimensions

Weight	3.920 lb (1.78 kg)
--------	--------------------

Conductor Related

Conductor Diameter – Maximum	1.824 in (46.79 mm)
Conductor Diameter – Minimum	1.632 in (41.45 mm)
Conductor Diameter Range	1.632 in – 1.824 in
Conductor Spacing	12 in (304.8 mm)
Conductor Type	AAC ACSR

RESOURCES AND DOWNLOADS

Specifications	Download PDF
Technical Drawings	Download PDF

For further technical assistance, please contact us

TTF Power Technology Co., Ltd.

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384

Landline: (+86) 22-8523-3528

Cell / WhatsApp: (+86) 155-1086-4645

Email: sales@ttfpower.com

Website: <https://ttfpower.com>