



Anchor Rod with Tripleye, Tensile Strength: 23,000 lb

Catalog ID: 03B4H2O

Anchor Rod with Tripleye
Application: Earth Tension Anchoring
Coating: Galvanized, ASTM A-153
Eyebut Style: Tripleye



PRODUCT DETAILS

General

Application	Earth Tension Anchoring
Coating	Galvanized, ASTM A-153
Eyebut Style	Tripleye
Strength Note	Ultimate strength ratings apply to properly installed anchors only. Failure to install within 5 ° of alignment with the guy load may significantly lower strength.
Tensile Strength	23000 lb
Type	Anchor Rod

Dimensions

Length	24.000 in (609.6 mm)
Rod Diameter	0.750 in (19.05 mm)
Weight	6.000 lb (2.72 kg)

Logistics

Carton Quantity	5
Pallet Quantity	160
Standard Package	5

RESOURCES AND DOWNLOADS

Specifications	Download PDF
Technical Drawings	Download PDF

For further technical assistance, please contact us

TTF Power Technology Co., Ltd.

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384

Landline: (+86) 22-8523-3528

Cell / WhatsApp: (+86) 155-1086-4645

Email: sales@ttfpower.com

Website: <https://ttfpower.com>