



Bonding Clamp

Catalog ID: 05E7Y5W

Bonding Clamp is used with grounding wires to connecting guy wires and stay wires. It is one kind of overhead line connectors. It meets your power and utility needs and requirements.
Body: Copper Alloy; Bolt: Silicon Bronze



PRODUCT DETAILS

General

Application	Bonding
Bolt Head Type	Hex
Bolt Installation Torque (Recommended)	180 in-lbs
Material	Copper Alloy
Material – Bolt	Silicon Bronze
Plating	Yes
Product Category	Communications Connectors

Dimensions

Bolt Diameter	0.31
Dimensions	1.410 in x 1.130 in x 0.460 in
Height	0.460 in (11.68 mm)
Length	1.410 in (35.81 mm)
Weight	0.200 lb (0.09 kg)
Width	1.130 in (28.7 mm)

Conductor Related

Conductor Diameter – Maximum	0.365
Conductor Diameter – Minimum	0.128
Conductor Diameter Range	0.128 – 0.365
Conductor Type	Copper Wire
Messenger Diameter – Maximum	0.438 in (11.13 mm)
Messenger Diameter – Minimum	0.25 in (6.35 mm)

Certifications and Compliance

UL Listed	Yes
-----------	-----

RESOURCES AND DOWNLOADS

Specifications	Download PDF
Technical Drawings	Download PDF

For further technical assistance, please contact us

TTF Power Technology Co., Ltd.

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384

Landline: (+86) 22-8523-3528

Cell / WhatsApp: (+86) 155-1086-4645

Email: sales@ttfpower.com

Website: <https://ttfpower.com>