



Cast Epoxy Cycloaliphatic Station Post Insulator

Catalog ID: 07F5P7Y

Station Post
Can be mounted upright or underhung



PRODUCT DETAILS

General

Application	Station Post Insulator
Bottom Terminal Type	Aluminum Threaded Inserts
Cantilever Bending Strength – Max.	2000
Cantilever Bending Strength – Routine	2000 lb (907.16 kg)
Color	Gray
Number of Bolt Holes – Bottom Terminal	4
Number of Bolt Holes – Top Terminal	4
Number of Sheds	9
Plating – Bottom Terminal	Unplated
Press Minimum	20000
Tensile Strength	10000 lb (4535.92 kg)
Top Terminal Plating	Unplated
Top Terminal Type	Aluminum Threaded Inserts
Type	Cast Epoxy Cycloaliphatic

Dimensions

Bottom Terminal Diameter	5.00 in (127 mm)
Diameter – Bottom Terminal Bolt Circle	3.00 in (76.2 mm)
Diameter – Bottom Terminal Bolt Holes	1/2-13
Diameter – Large Shed	5.00 in (127 mm)
Diameter – Top Terminal Bolt Circle	3.00 in (76.2 mm)
Diameter – Top Terminal Bolt Holes	1/2-13
Diameter – Top Terminal Outside	4.50 in (114.3 mm)
Length	10.00 in (254 mm)
Weight	10.0 lb (4.54 kg)

Electrical Ratings

Minimum Creepage	20.8 in (528.32 mm)
Minimum Strike	10.00 in (254 mm)
kV Class	15 kV

Certifications and Compliance

Industry Standard(s)	ANSI C29.9
----------------------	------------

RESOURCES AND DOWNLOADS

Specifications	Download PDF
Technical Drawings	Download PDF

For further technical assistance, please contact us

TTF Power Technology Co., Ltd.

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384

Landline: (+86) 22-8523-3528

Cell / WhatsApp: (+86) 155-1086-4645

Email: sales@ttfpower.com

Website: <https://ttfpower.com>