



Compression Splices

Catalog ID: 01C7C8J

Compression Splice

Industrial standard ANSI C119.4

A super durable or impermanent association on AAC, ACSR or AAAC conductor
 Conductor type 397.5, 336.4 AAC, 394.5 AAAC, 336.4(18/1) ACSR

Applications on full or partial tension

Against corrosion



PRODUCT DETAILS

General

Aluminum Die	27AH
Compression Method	Conventional (2 die system)
Material	Aluminum; Steel
Press Minimum	60 to

Dimensions

Diameter – Outside	1.014 in (25.76 mm)
Length Before Compression	32.18 in (817.37 mm)

Electrical Ratings

Voltage Application	EHV; Standard
---------------------	---------------

Conductor Related

Conductor Compatibility	ACSS-Gannet-666.6-26/7
Conductor Type	ACSS

RESOURCES AND DOWNLOADS

Specifications	Download PDF
Technical Drawings	Download PDF

For further technical assistance, please contact us

TTF Power Technology Co., Ltd.

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384

Landline: (+86) 22-8523-3528

Cell / WhatsApp: (+86) 155-1086-4645

Email: sales@ttfpower.com

Website: <https://ttfpower.com>