



Copper Split Bolt Connector, Range 0.232 in – 0.373 in

Catalog ID: 09D7E4M

Copper Split Bolt Connector
 CSA Approved Certification and UL Listed
 RoHS Compliance Status Standards CM
 High-strength solderless assistance connectors



PRODUCT DETAILS

General

Bolt Head Type	Hex
Item Type	4D
Material	Copper
Material – Body	Copper Alloy
Plating Type	Unplated
Product Category	Mechanical Connectors
Style	Split Bolt

Dimensions

Bolt Diameter	0.38 in (9.65 mm)
Weight	0.157 lb (0.07 kg)

Conductor Related

Conductor Diameter (Tap) – Maximum	0.373 in (9.47 mm)
Conductor Diameter – Maximum	0.373 in (9.47 mm)
Conductor Diameter – Minimum	0.232 in (5.89 mm)
Conductor Diameter Range	0.232 in – 0.373 in

Logistics

Pallet Quantity	14400
-----------------	-------

RESOURCES AND DOWNLOADS

Specifications	Download PDF
Technical Drawings	Download PDF

For further technical assistance, please contact us

TTF Power Technology Co., Ltd.

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384

Landline: (+86) 22-8523-3528

Cell / WhatsApp: (+86) 155-1086-4645

Email: sales@ttfpower.com

Website: <https://ttfpower.com>