



Copper Split Bolt Connector, Weight: 0.206 lb

Catalog ID: 09D8B2S

Copper Split Bolt Connector is one kind of line construction hardware, pole line fittings and components. It meet your power and utility needs.

The Split Bolt Connector is made of copper for its conductive shilling shilling of boot and

The Split Bolt Connector is made of copper for its conductive ability of heat and electricity.



PRODUCT DETAILS

General

Bolt Head Type	Hex	
Item Type	4D	
Material	Copper	
Material – Body	Copper Alloy	
Material – Spacer	Copper Alloy	
Plated	N	
Plating Type	Unplated	
Product Category	Mechanical Connectors	
Style	Split Bolt	

Dimensions

Weight	0.206 lb (0.09 kg)
č	(8)

Conductor Related

Conductor Diameter (Tap) – Maximum	0.419 in (10.64 mm)
Conductor Diameter (Tap) – Minimum	0.146 in (3.71 mm)
Conductor Diameter – Maximum	0.418
Conductor Diameter – Minimum	0.292
Conductor Diameter Range	0.292 - 0.418

Certifications and Compliance

Certification – CSA Approved	Yes
Certification – ETL	No
Certification – UL Recognized	N
Certification – cULus	N
Standards – RoHS Compliance Status	CM

UL Listed Yes

RESOURCES AND DOWNLOADS

Specifications	Download PDF
Technical Drawings	Download PDF

For further technical assistance, please contact us

TTF Power Technology Co., Ltd.

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384

Landline: (+86) 22-8523-3528

Cell / WhatsApp: (+86) 155-1086-4645

Email: sales@ttfpower.com Website: https://ttfpower.com