



Copper Split Bolt, Range 0.332 in – 0.47 in

Catalog ID: 09D1C9Z

Split Bolt
with cable separator
Detailed specification in PDF



PRODUCT DETAILS

General

Bolt Head Type	Hex
Cover Available	No
Inhibitor Loaded	No
Item Type	4D
Material	Copper
Material – Body	Copper Alloy
Plated	N
Plating	No
Plating Type	Unplated
Product Category	Mechanical Connectors
Style	Split Bolt

Conductor Related

Conductor Diameter (Tap) – Maximum	0.47 in (11.94 mm)
Conductor Diameter (Tap) – Minimum	0.146 in (3.71 mm)
Conductor Diameter – Maximum	0.47 in (11.94 mm)
Conductor Diameter – Minimum	0.332 in (8.43 mm)
Conductor Diameter Range	0.332 in – 0.47 in

Certifications and Compliance

Certification – CSA Approved	Yes
Certification – ETL	No
Certification – UL Recognized	N
Certification – cULus	N
Standards – RoHS Compliance Status	UI
UL Listed	Yes

Logistics

Pallet Quantity	5760
-----------------	------

RESOURCES AND DOWNLOADS

Specifications	Download PDF
Technical Drawings	Download PDF

For further technical assistance, please contact us

TTF Power Technology Co., Ltd.

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384

Landline: (+86) 22-8523-3528

Cell / WhatsApp: (+86) 155-1086-4645

Email: sales@ttfpower.com

Website: <https://ttfpower.com>