



D-shape Loadbreak Polymer Cutout, Maximum Voltage: 15 kV

Catalog ID: 02C1M2I

The D-shape Loadbreak Polymer Cutout is a kind of electrical equipment. It stops the flow of electrical current by quickly extinguishing an arc which is generated inside the fuse holder. It protect your safety in electricity application inside your house.



PRODUCT DETAILS

General

racket Type	NEMA "B" Heavy Duty for crossarm
Description – Replacement Fuse Holder	T730-143T
EU RoHS Indicator	No
Type	Cutout

Electrical Ratings

BIL	110 kV
Creep and Leakage Distance	12.6" (319mm)
Current Rating	200 A
Fuselink Current Range	140A to 200A – removable buttonhead fuse link only
Reference Voltage Limit – Minimum	Thru 14.4kV
Temperature Rise – Max. at 300A	39° C
Voltage – Maximum	15 kV
Voltage – Radio Interference	Ambient @ 9.41kV
Voltage Rating	15 kV

Logistics

Standard Package	1
------------------	---

RESOURCES AND DOWNLOADS

Specifications	Download PDF
Technical Drawings	Download PDF

For further technical assistance, please contact us

TTF Power Technology Co., Ltd.

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384

Landline: (+86) 22-8523-3528

Cell / WhatsApp: (+86) 155-1086-4645

Email: sales@ttfpower.com

Website: <https://ttfpower.com>