



## D-shape Loadbreak Polymer Cutout with a 100A, 10kAIC Fuseholder

Catalog ID: 02C1U1R

D-shape Loadbreak Polymer Cutout with a 100A, 10kAIC Fuseholder  
 Cut off the electrical current flow in wire and cables  
 Protect human beings and animals from lightning and storms as well as other extreme weathers  
 Different types available: loadlink cutout fuse, linkbreak cutout fuse and standard cutout fuse



### PRODUCT DETAILS

#### General

Bracket Type	NEMA "B" Heavy Duty for crossarm
Type	Cutout

#### Dimensions

Weight	4.41 lb (2 kg)
--------	----------------

#### Electrical Ratings

BIL	110 kV
Creep and Leakage Distance	12.6" (319mm)
Current Rating	100 A
Fuselink Current Range	1A to 100A
Reference Voltage Limit – Minimum	Thru 14.4kV
Temperature Rise – Max. at 300A	39° C
Voltage – Maximum	15 kV
Voltage – Radio Interference	Ambient @ 9.41kV
Voltage Rating	15 kV

#### Logistics

Pallet Quantity	24
Standard Package	1

### RESOURCES AND DOWNLOADS

Specifications	<a href="#">Download PDF</a>
----------------	------------------------------

*For further technical assistance, please contact us*

**TTF Power Technology Co., Ltd.**

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384

Landline: (+86) 22-8523-3528

Cell / WhatsApp: (+86) 155-1086-4645

Email: [sales@ttfpower.com](mailto:sales@ttfpower.com)

Website: <https://ttfpower.com>