



## Distribution Arrester, 10.2 KV MCOV

Catalog ID: 08A8Z5C

Distribution Arrester  
specific details in PDF



### PRODUCT DETAILS

#### General

Application	Distribution
Bracket Type	None
Color	Gray
Material	Silicone Polymer Housing
Mounting Position	Upright
Type	5 kA

#### Dimensions

Stud Type	M12
-----------	-----

#### Electrical Ratings

Creep and Leakage Distance	390 mm
Current – Low Current Long Duration (LCLD) Test	75
Duty Cycle	12 kV
Frequency Rating	48-62 Hz
MCOV	10.2 kV
Maximum .5 Microsecond Discharge Volts @ Classifying Current	40.0 kV
Maximum Discharge Voltage	32.9 kV @ 1.5 kA 35.6 kV @ 3 kA 36.9 kV @ 5 kA 40.6 kV @ 10 kA 46.1 kV @ 20 kA 54.7 kV @ 40 kA
Maximum Switching Surge Protective Level @ 500A	27.8 kV
Minimum Strike	155.0 mm
Pressure Relief Capability-Symmetrical rms (kA)	15
Time – Low Current Long Duration (LCLD) Test	2000 $\mu$ s
Withstand Voltage – 60 Hz Wet	34

Withstand Voltage – Lightning Impulse	125
Withstand Voltage – Switching Impulse	31.3

---

## RESOURCES AND DOWNLOADS

---

Specifications	<a href="#">Download PDF</a>
Technical Drawings	<a href="#">Download PDF</a>

---

*For further technical assistance, please contact us*

**TTF Power Technology Co., Ltd.**

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384

Landline: (+86) 22-8523-3528

Cell / WhatsApp: (+86) 155-1086-4645

Email: [sales@ttfpower.com](mailto:sales@ttfpower.com)

Website: <https://ttfpower.com>