



D-Shaped Linkbreak Type C Cutout Fuse with a 100 A, 10kAIC Fuseholder

Catalog ID: 02B3S90



D-Shaped Linkbreak Type C Cutout Fuse with a 100 A, 10kAIC Fuseholder
 Cut off the electrical current flow in wire and cables
 Protect human beings and animals from lightning and storms as well as other extreme weathers
 Different types available: loadlink cutout fuse, linkbreak cutout fuse and standard cutout fuse

PRODUCT DETAILS

General

Bracket Type	Extended NEMA “B” for crossarm
Type	Cutout

Dimensions

Weight	10.741 lb (4.87 kg)
--------	---------------------

Electrical Ratings

BIL	110 kV
Creep and Leakage Distance	12.6” (319mm)
Current Rating	100 A
Fuselink Current Range	1A to 100A
Reference Voltage Limit – Minimum	Thru 14.4kV
Temperature Rise – Max. at 300A	38° C
Voltage – Maximum	15 kV
Voltage – Radio Interference	Ambient @ 9.41kV
Voltage Rating	15 kV

Logistics

Pallet Quantity	63
Standard Package	1

RESOURCES AND DOWNLOADS

Specifications	Download PDF
----------------	--------------

For further technical assistance, please contact us

TTF Power Technology Co., Ltd.

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384

Landline: (+86) 22-8523-3528

Cell / WhatsApp: (+86) 155-1086-4645

Email: sales@ttfpower.com

Website: <https://ttfpower.com>