



D-Shaped Loadbreak Type C Cutout Fuse with 10kAIC Fuseholder

Catalog ID: 02C9F2R

Loadbreak Cutout fuse
 BIL 15kv, 110kv
 with a small eyebolt connector



PRODUCT DETAILS

General

Bracket Type	D-shape for pole mounting
Description – Replacement Fuse Holder	T730-112T
Type	Cutout

Electrical Ratings

BIL	110 kV
Creep and Leakage Distance	12.6 in (319mm)
Current Rating	100 A
Fuselink Current Range	1A to 100A
Reference Voltage Limit – Minimum	Thru 14.4kV
Temperature Rise – Max. at 300A	39° C
Voltage – Maximum	15 kV
Voltage – Radio Interference	Ambient @ 9.41kV
Voltage Rating	15 kV

Logistics

Standard Package	1
------------------	---

RESOURCES AND DOWNLOADS

Specifications	Download PDF
Technical Drawings	Download PDF

For further technical assistance, please contact us

TTF Power Technology Co., Ltd.

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384

Landline: (+86) 22-8523-3528

Cell / WhatsApp: (+86) 155-1086-4645

Email: sales@ttfpower.com

Website: <https://ttfpower.com>