



## D-Shaped Standard Type C Cutout Fuse with 10kAIC Fuseholder

Catalog ID: 02A6W9P

Standard Cutout fuse  
 BIL 15 kV, 110 kv  
 Detailed specification in PDF



### PRODUCT DETAILS

#### General

Bracket Type	D-shape for pole mounting
Description – Replacement Fuse Holder	T710-112TM
Type	Cutout

#### Electrical Ratings

BIL	110 kV
Creep and Leakage Distance	12.6" (319mm)
Current Rating	100 A
Fuselink Current Range	1A to 100A
Reference Voltage Limit – Minimum	Thru 14.4kV
Temperature Rise – Max. at 300A	38° C
Voltage – Maximum	15 kV
Voltage – Radio Interference	Ambient @ 9.41kV
Voltage Rating	15 kV

#### Logistics

Pallet Quantity	63 EA
Standard Package	1

### RESOURCES AND DOWNLOADS

Specifications	<a href="#">Download PDF</a>
Technical Drawings	<a href="#">Download PDF</a>

*For further technical assistance, please contact us*

**TTF Power Technology Co., Ltd.**

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384

Landline: (+86) 22-8523-3528

Cell / WhatsApp: (+86) 155-1086-4645

Email: sales@ttfpower.com

Website: <https://ttfpower.com>