



Double Pin Tie

Catalog ID: 01A5X7D

Double Side Tie is one kind of connectors used on overhead line construction. It is manufactured of composite material. Its cover and body is made of rigid black PVC.

It is designed to secure conductors on double-arm construction in the power line hardware systems.



PRODUCT DETAILS

General

Color Code	Orange
Insulator Throat Neck Type	C Neck
Material	Composite
Material – Cover and Body	Semi-Conductive covering over Rigid Black PVC
Product Category	Ties

Dimensions

Insulator Throat Diameter – Maximum	2.75 in (69.85 mm)
Insulator Throat Diameter – Minimum	2.12 in (53.85 mm)
Insulator Throat Diameter Range	2.12 - 2.75
Length	13.000 in (330.2 mm)
Weight	0.363 lb (0.16 kg)

Conductor Related

Conductor Diameter (Covered) – Maximum	0.919 in (23.34 mm)
Conductor Diameter (Covered) – Minimum	0.718 in (18.24 mm)
Conductor Diameter (Covered) Range	0.919-0.718
Conductor Diameter – Maximum	0.919
Conductor Diameter – Minimum	0.718
Conductor Diameter Range	0.718 - 0.919
Conductor Type	Covered

Logistics

RESOURCES AND DOWNLOADS

Specifications	Download PDF
Technical Drawings	Download PDF

For further technical assistance, please contact us

TTF Power Technology Co., Ltd.

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384 Landline: (+86) 22-8523-3528 Cell / WhatsApp: (+86) 155-1086-4645 Email: sales@ttfpower.com Website: https://ttfpower.com