



Downlead Bracket

Catalog ID: 06K8R9J

Fiberglass Downlead Bracket-line construction hardware Construction bracket It is designed for supporting other electrical line accessories and components. End Fitting: Cable Clamp



PRODUCT DETAILS

General

Description – End Fitting	Cable Clamp
Dimensions	
Diameter – Rod / Tube	0.625 in (15.88 mm)
Distance From Pole	12 in (304.8 mm)
Length	12.00 in (304.8 mm)
Mounting Bolt Spacing	0.6875 in (17.46 mm)
Weight	1.9 lb (0.86 kg)
Conductor Related	
Conductor Diameter – Maximum	0.398 in (10.11 mm)
Conductor Diameter – Minimum	0.128 in (3.25 mm)
Logistics	
Pallet Quantity	720
Standard Package	5
RESOURCES AND DOWNLOADS	
Specifications	Download PDF
Technical Drawings	Download PDF

For further technical assistance, please contact us

TTF Power Technology Co., Ltd.

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384

Landline: (+86) 22-8523-3528

Cell / WhatsApp: (+86) 155-1086-4645

Email: sales@ttfpower.com Website: https://ttfpower.com