



Expanding Rock Anchor with Tripleye, Tensile Strength: 23000 lb

Catalog ID: 03G3G70

Rock Anchor with Tripleye is designed to stabilize the foundation of the construction and avoid its movement. It is a kind of power line fittings and hardware. It adopts Galvanized, ASTM A-153 galvanizing standard to coat rock anchor.
Tensile Strength: 23000 lb



PRODUCT DETAILS

General

Application	Earth Tension Anchoring
Coating	Galvanized, ASTM A-153
EU RoHS Indicator	No
Eyenuit Style	Tripleye
Strength Note	Ultimate strength ratings apply to properly installed anchors only. Failure to install within 5° of alignment with the guy load may significantly lower strength. Recommended minimum installation depth is 12" in solid rock.
Tensile Strength	23000 lb
Type	Rock Anchors

Dimensions

Anchor Hole Size	2 in (50.8 mm)
Diameter	1.75 in (44.45 mm)
Length	53.000 in (1346.2 mm)
Rod Diameter	0.750 in (19.05 mm)
Weight	9.408 lb (4.27 kg)

Certifications and Compliance

RUS Listed Reference	z – Anchors, Rock
----------------------	-------------------

Logistics

Pallet Quantity	50
Standard Package	5

RESOURCES AND DOWNLOADS

Specifications	Download PDF
----------------	------------------------------

For further technical assistance, please contact us

TTF Power Technology Co., Ltd.

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384

Landline: (+86) 22-8523-3528

Cell / WhatsApp: (+86) 155-1086-4645

Email: sales@ttfpower.com

Website: <https://ttfpower.com>