



Fiberglass Secondary Connector or Sectionalizer, Length 18.8 in, With HDG Ductile Iron End Fittings

Catalog ID: 05C1L5D

Secondary Connector
guarantee water tight association alongside consistent power and correspondence
also called Secondary Sectionalizer or split
Two types plug and socket



PRODUCT DETAILS

General

Description – End Fitting	HDG Ductile Iron
Strength Rating – Minimum Ultimate, Longitudinal (L)	6000 lb (2721.55 kg)

Dimensions

Diameter – Rod / Tube	0.625 in (15.88 mm)
Distance From Pole	18.8 in (477.52 mm)
Length	18.8 in (477.52 mm)
Radius – FWDE Wrap-Around	0.625 in (15.88 mm)
Weight	4.0 lb (1.81 kg)

Logistics

Standard Package	1
------------------	---

RESOURCES AND DOWNLOADS

Specifications	Download PDF
Technical Drawings	Download PDF

For further technical assistance, please contact us

TTF Power Technology Co., Ltd.

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384

Landline: (+86) 22-8523-3528

Cell / WhatsApp: (+86) 155-1086-4645

Email: sales@ttfpower.com
Website: <https://ttfpower.com>