



Galvanized Rod Anchor with Three Eyes, Rod Diameter 0.75 in

Catalog ID: 03G6A7T



Rock Anchor
 Can be wedged in to the solid wall
 The more the wall expands, the greater the tension
 Material cast iron
 Easy installation with instruction
 minimum depth of 12 in

PRODUCT DETAILS

General

Application	Earth Tension Anchoring
Coating	Galvanized
Eyenuit Style	Tripleye
Strength Note	Ultimate strength ratings apply to properly installed anchors only. Failure to install within 5° of alignment with the guy load may significantly lower strength. Recommended minimum installation depth is 12" in solid rock.
Tensile Strength	23000 lb (10432.62 kg)
Type	Rock Anchors

Dimensions

Anchor Hole Size	2 in (50.8mm)
Diameter	1.75 in (44.4 mm)
Length	30 in (762 mm)
Rod Diameter	0.75 in (19.05 mm)

Logistics

Pallet Quantity	50 EA
Standard Package	5

RESOURCES AND DOWNLOADS

Specifications	Download PDF
Technical Drawings	Download PDF

For further technical assistance, please contact us

TTF Power Technology Co., Ltd.

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384

Landline: (+86) 22-8523-3528

Cell / WhatsApp: (+86) 155-1086-4645

Email: sales@ttfpower.com

Website: <https://ttfpower.com>