



Galvanized Rod Anchor with Three Eyes, 30 in Length

Catalog ID: 03G1A3E

Rock Anchor Length 30 in minimum depth of 12 in



PRODUCT DETAILS

Application	Earth Tension Anchoring
Coating	Galvanized, ASTM A-153
Eyenut Style	Three eye
Strength Note	Ultimate strength ratings apply to properly installed anchors only Failure to install within 5° of alignment with the guy load may significantly lower strength. Recommended minimum installation depth is 12″ in solid rock.
Tensile Strength	23000 lb (10432.62 kg)
Туре	Rock Anchors
Dimensions	
Anchor Hole Size	2 in (50.8 mm)
Diameter	1.75 in (44.45 mm)
Rod Diameter	0.75 in (19.05 mm)
Certifications and Compliance	
RUS Listed Reference	z – Anchors, Rock
Logistics	
Pallet Quantity	50
Standard Package	5

Specifications	Download PDF
Technical Drawings	Download PDF

For further technical assistance, please contact us

TTF Power Technology Co., Ltd.

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384 Landline: (+86) 22-8523-3528 Cell / WhatsApp: (+86) 155-1086-4645 Email: sales@ttfpower.com Website: https://ttfpower.com