



## Insulated Secondary Clevis

**Catalog ID: 04C8F9Y**

Insulated Secondary Clevis is used with spool insulators. It is one kind of line construction hardware. Spool Insulator Used to give give assurance to guides on low voltage electrical links. Also called a shackle insulator or a butterfly insulator.



### PRODUCT DETAILS

#### General

Coating	Galvanized, ASTM A-153
Material	Steel
Type	Insulated Secondary Clevis

#### Dimensions

Distance From Pole	N/A
Height	3.50 in (88.9 mm)
Length	4.00 in (101.6 mm)
Weight	1.33 lb (0.6 kg)

#### Certifications and Compliance

Industry Standard(s)	ANSI C135.20
----------------------	--------------

#### Logistics

Pallet Quantity	1120
-----------------	------

### RESOURCES AND DOWNLOADS

Specifications	<a href="#">Download PDF</a>
Technical Drawings	<a href="#">Download PDF</a>

*For further technical assistance, please contact us*

**TTF Power Technology Co., Ltd.**

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384

Landline: (+86) 22-8523-3528

Cell / WhatsApp: (+86) 155-1086-4645

Email: [sales@ttfpower.com](mailto:sales@ttfpower.com)

Website: <https://ttfpower.com>