



## Power Installed Screw Anchor

Catalog ID: 03F9C6J

Anchor rods are fasteners used for supporting power poles and utility poles. They are installed in concrete foundations. It can be used with screw anchors. It is coated by galvanizing standard—Galvanized, ASTM A-153.



### PRODUCT DETAILS

#### General

Application	Helical Anchoring
Coating	Galvanized, ASTM A-153
Strength Note	Ultimate strength ratings apply to properly installed anchors only. Failure to install within 5 ° of alignment with the guy load may significantly lower strength.
Tensile Strength	36000 lb
Type	Power Installed Screw Anchor (PISA)

#### Dimensions

Length	42.000 in (1066.8 mm)
Rod Diameter	1.000 in (25.4 mm)
Weight	9.820 lb (4.45 kg)

#### Logistics

Pallet Quantity	50
Standard Package	5

### RESOURCES AND DOWNLOADS

Specifications	<a href="#">Download PDF</a>
Technical Drawings	<a href="#">Download PDF</a>

*For further technical assistance, please contact us*

**TTF Power Technology Co., Ltd.**

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384  
Landline: (+86) 22-8523-3528

Cell / WhatsApp: (+86) 155-1086-4645

Email: [sales@ttfpower.com](mailto:sales@ttfpower.com)

Website: <https://ttfpower.com>